






SPECIFICATION

Current Rating: 3 AMP
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.
 Dielectric Voltage: 500V AC for one minute
 Operation Temperature: -40°C to +105 °C

MATERIAL

Insulator: Hi-Temp. Thermoplastic, UL94V-0, Black
 Contact Pin: Copper Alloy

ORDER INFORMATION



Recommended PCB Layout
 (PCB TOLERANCE ±0.1)

Old Part No. : PH1RDL25-2XX-U

REV.	Modify order information	B	2017/01/25 Gary
	ECN NO. OR DESCRIPTION	REVISED	DATE

Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 2.54mm D/R R/A DIP TYPE				頁數 Page	1/1
品號 PART NO.	5PH1RLA25-2XXXXNNXU -XXXXXXXXX-00			繪圖 DRAWN	Mia 2016/09/22	
圖號 DRAWING NO.	GN016-GA151	版本 REV.	B	核對 CHECKED	Jonny 2016/09/22	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Aaron 2016/09/22	
公差 TOLERANCE	.X ± 0.35 .XX ± 0.25	單位 UNIT	mm	THIRD ANGLE PROJECTION		