


SPECIFICATIONS:

- Contact Rating: 5A @ 250VAC.
- Electrical Life: 50,000cycles.
- Contact Resistance: 50m-ohms max (initial).
- Insulation Resistance: 1,000M-ohms min @ 500VDC.
- Dielectric Strength: 2,000V RMS 50~60Hz.
- Operating Temperature: -20°C ~ +55°C.
- Switching Type: 90° 2 positions ON-MOM (return).
- Protection Class: IP40 & IK03 protection.
- Torque: 5~14Nm max. applied to nut.

MATERIALS:

- Bushing & Button: Refer to below table
- Contact: Silver alloy.
- Nut: Nickel plated brass.
- Base: PBT.

Key Position



Wiring Diagram

- C-NC: Ring - No illumination
- C-NO: Ring - Red & Green

"x"	LED Color
R	Red
G	Green
Y	Yellow
O	Orange
B	Blue
W	White

Code	Bushing & Button Material
BB2	Stainless steel with varnished polished

ITEM NO. 料號	AV02L-BB2-M3-KC2-RG-24V
----------------	-------------------------

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TAIWAY ELECTRONICS COMPONENTS LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF TAIWAY ELECTRONICS COMPONENTS LTD.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°

DIMENSIONS	TOLERANCE
0.00 TO 10.00mm	±0.20mm
10.01 TO 20.00mm	±0.25mm
20.01 TO 30.00mm	±0.30mm
30.01	±0.40mm

泰瑋電子有限公司 TAIWAY ELECTRONICS COMPONENTS CO.,LTD.			
USED 用途	AV	APPD. 審核	Amy 2014/05/21
FINISH 處理		CHKD. 校對	Amy 2014/05/21
SCALE 比例	2 / 1	UNIT 單位	in(mm)
		DR. 製圖	Amy 2014/05/21
TITLE 名稱	Anti-Vandal Switch		
DWG NO. 圖號	AV02L-BB2-M3-KC2-RG-x		SIZE 圖紙
FILE NAME 檔案名稱	AV02L-BB2-M3-KC2.DWG	SHEET 張	1 / 1
		REV. 更改	1